

# Technical Data Sheet

Prouct name	Zinc Oxide ( AP-1 )
Chemical formula	ZnO
Appearance	Grayish white Powder
Storage	Keep in tightly closed. Keep in a cool, well - ventilated area. Do not store above 25°C
Packing unit	20Kg Craft Wrapping paper, 500Kg Poly Propylene Woven Bag It is possible to control the bag size on their customer needs
characteristics & Application	ZnO has high refractive index, good thermal, binding, antibacterial and UV-protection properties. Consequently, It is added into various materials, including plastics, ceramics, glass, cement, rubber, lubricants, paints, adhesive, sealants, pigments, foods, batteries, ferrites, fire retardants, etc.

## CHEMICAL ANALYSIS

ITEM	UNIT	SPECIFICATION	ANALYTIC METHODS
ZnO	wt.%	94.0 Min	KS M 6551 ASTM D 3280
Pb	wt.%	3.00 Max	KS M 0032(ICP-AES) ASTM D 4075
Cd	wt.%	0.10 Max	
Fe	wt.%	0.10 Max	
Moisture (105°C)	wt.%	0.30 Max	KS M 6551 ASTM D 280
Sieve Residue (+ 325 mesh)	wt.%	0.40 Max	KS M 6551 ASTM D 4315
Water Soluble	wt.%	0.10 Max	KS M 6551
Sp. Gravity	--	5.47~5.61	KS M 0004

Office	612, Seolleung-ro, Gangnam-gu, Seoul, Korea		
Telephone	82-2-3448-4257		
Facsimile	82-2-3448-4269		
Email : kwkeum@hanzinc.com	Web site : www.hanzinc.com		
Factory	37, Gongdan 1-daero, Siheung-si, Gyuenggi-do, Korea		
Telephone	82-31-499-8201~6		
Facsimile	82-31-499-8207		
Email : igjung@hanzinc.com	Web site : www.hanzinc.com		

HANIL CHEMICAL IND. CO.,LTD.